

INSTRAN

instran ®



ON-LINE ANALYZER
WATER QUALITY PARAMETERS

FEATURES



ACCURACY

Accuracy, repeatability and reliability



LOW MAINTENANCE

Low maintenance required due to Instran design



ROBUSTNESS

Robustness thanks to spares are manufactured by the best materials



AUTONOMY

Low consumption of reagents to increase autonomy



ADAPTABLE

Auto-cleanings available to adapt the analyzer to waste water samples



POWERFUL

Ability to run different functions and flexible to program easily

MODELS & PARAMETERS

COLORIMETRIC

Concentration determination after calculating the absorbance and using Beer-Lambert law

Aluminium (Al)

Boron (B)

Copper (Cu)

Chromium VI - Chromium Total [Cr (VI) - Cr Total]

Cyanide (CN)

Cyanuric Acid (C₃H₃N₃O₃)

Iron (Fe)

Manganese (Mn)

Nickel (Ni)

Nitrite (NO₂-)

Phenol (C₆H₆O)

Phosphate (PO₄)

Silica (SiO₂)

Chlorate (ClO₃-)

ISE (Ion Selective Electrode)

Ion selective electrode used to determine the concentration according to Nernst equation

Ammonium (NH₃ - NH₄)

Chloride (Cl⁻)

Chlorine (Cl₂)

Fluoride (F⁻)

Nitrate (NO₃-)

Sodium (Na⁺)

TITRATION

Colorimetric or ISE titration, depending on the type of measurement

Alkalinity

Boron (High Range)

Chlorine (High Range)

Calcium hardness

Total hardness



instran ®

PRODUCT SPECIFICATIONS



CLEANINGS	Scheduled cleanings before and after each analysis with sample, DIW or specific solution
ANALYSIS CORRECTIONS	Temperature correction Blank correction LED current correction
DOSE SYSTEM	Syringe driven by step by step motor Accuracy: 0.015 ml
FLUID SYSTEM	Loop to protect the syringe Valves made of Kalrez High resistance tubing (Tygon 2375) Complete system without fittings
REACTION VESSEL	Low volume glass vessel (17ml) Automatic system to prevent overflow Special design to make drain easier
SAMPLE CAPTURE -FAST LOOP	Inlet: 6 mm tub. Outlet: 8 mm tub. Fast Loop Inlet Sample level detector Anti-overflow system Manual valve to drain while manual cleaning
ENVIRONMENTAL CONDITIONS	0°C to 45°C
POWER	Input: AC 100-240V - 50Hz Max Power: 288 W
SET UP	Steel frame IP66 enclosure
SIZE	Steel frame: 65x40x15 cm IP66 enclosure: 75x55x30 cm
USER INTERFACE	Keypad with 4 keys and 4 indication LEDs
LANGUAGES	English, Spanish
COMMUNICATIONS	4-20 mA signal RS-485 communication RS485 MODBUS or PROFIBUS
RELAYS	4 relays (24V), assigned by user
DIAGNOSTIC MENU	Self- evaluation of analyzer status
CALIBRATION & ANALYSIS	Manual or Automatic

Innovation and Technology at your Service



Follow us:



Visit
Our web

 instrumentación analítica, s.a.

Calle Penedes, 46
08820, Barcelona
Tel. +34-93.4787161
instran@instran.net
c.salinas@instran.net

www.instran.net